		Page: 1
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
		SDS Number: R1600370
CAN HTH EXTRA DURATION PUCKS		Version: 1.2
891045		

SECTION 1. IDENTIFICATION

Product identifier

Trade name : CAN HTH EXTRA DURATION PUCKS

Recommended use of the chemical and restrictions on use

Use of the Substance/Mixture : Pesticide

Details of the supplier of the safety data sheet Innovative Water Care, LLC 1400 Bluegrass Lakes Parkway Alpharetta, GA 30004 Canada EHSProductSafetyTeam@solenis.com	Emergency telephone 1-800-654-6911 (Outside the USA:1-423-780-2970) Product Information 1-800-511-6737 (Outside the USA:1-423-780-2347)
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations


Oxidizing solids : Category 2
 Acute toxicity (Oral) : Category 4
 Skin corrosion : Category 1B
 Serious eye damage : Category 1
 Specific target organ toxicity : Category 3 (Respiratory system)
 - single exposure

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H272 May intensify fire; oxidizer.
 H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H335 May cause respiratory irritation.

		Page: 2
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
		SDS Number: R1600370
CAN HTH EXTRA DURATION PUCKS		Version: 1.2
891045		

Precautionary Statements :

Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P220 Keep away from clothing and other combustible materials.
- P260 Do not breathe dust.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

- P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
- P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
- P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
- P363 Wash contaminated clothing before reuse.
- P370 + P378 In case of fire: Use water spray to extinguish.

Storage:

- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.

Disposal:

- P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards


None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
CALCIUM HYPOCHLORITE	7778-54-3	>= 70 - < 80
CALCIUM HYDROXIDE	1305-62-0	>= 10 - < 15


		Page: 3
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
		SDS Number: R1600370
CAN HTH EXTRA DURATION PUCKS		Version: 1.2
891045		

CALCIUM CHLORIDE	10043-52-4	>= 1.5 - < 5
CALCIUM CARBONATE	471-34-1	>= 1.5 - < 5

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Do not leave the victim unattended.
Move to fresh air.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If on clothes, remove clothes.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Get medical attention immediately.
Do NOT induce vomiting.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
discomfort in the chest
bronchitis
Headache
Shortness of breath
lung edema (fluid buildup in the lung tissue)
Pulmonary edema may be delayed.
Harmful if swallowed.
Causes serious eye damage.
May cause respiratory irritation.
Causes severe burns.

		Page: 4
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
		SDS Number: R1600370
CAN HTH EXTRA DURATION PUCKS		Version: 1.2
891045		

Notes to physician : Probable mucosal damage may contraindicate the use of gastric lavage.

SECTION 5. FIRE-FIGHTING MEASURES


- Suitable extinguishing media : Water
- Unsuitable extinguishing media : Dry extinguishers containing ammonium compounds.
- Specific hazards during fire fighting : May intensify fire, oxidizer.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Chlorine
- Further information : Use water to cool containers exposed to fire.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Avoid dust formation.
Avoid breathing dust.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Sweep up and shovel using a clean broom or shovel.
Shovel material into clean dry containers.
All spills of this product should be treated as contaminated.
Contaminated product may initiate a chemical reaction that may spontaneously ignite any combustible material present, resulting in a fire.
Avoid getting spilled product wet.
Do not seal disposal containers tightly. Immediately remove all product in disposal containers to an isolated area outdoors.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against : Keep away from combustible material.

		Page: 5
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
		SDS Number: R1600370
CAN HTH EXTRA DURATION PUCKS		Version: 1.2
891045		

- fire and explosion : Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Avoid dust formation.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapors/dust.
Do not smoke.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.


Store in original container.
- Recommended storage temperature : <= 35 °C
- Further information on storage stability : Do not store next to a heat source, in direct sunlight, or elevated temperatures. Do not store where the daily average temperature exceeds prescribed storage temperature for 7 consecutive days. Prevent ingress of humidity and moisture into container or package. Keep containers tightly closed.

Maximum average daily temperature as recommended (where the average daily temperature may be obtained by averaging the minimum and maximum temperatures for each day).
Storage above this temperature may result in rapid decomposition, evolution of chlorine gas and heat sufficient to ignite combustible products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
CALCIUM HYDROXIDE	1305-62-0	TWA	5 mg/m ³	CA AB OEL
		TWA	5 mg/m ³	CA BC OEL

		Page: 6
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
		SDS Number: R1600370
CAN HTH EXTRA DURATION PUCKS		Version: 1.2
891045		

		TWAEV	5 mg/m3	CA QC OEL
CALCIUM CHLORIDE	10043-52-4	TWA	5 mg/m3	CA ON OEL
CALCIUM CARBONATE	471-34-1	TWAEV (total dust)	10 mg/m3	CA QC OEL
		TWA	10 mg/m3 (Calcium carbonate)	CA AB OEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Provide appropriate exhaust ventilation at places where dust is formed.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.
Dust safety masks are recommended when the dust concentration is more than 10 mg/m3.


Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles and face shield to protect eyes and skin from airborne dust.
Maintain eye wash station in immediate work area.


Skin and body protection : Wear as appropriate:
Chemical resistant apron
Safety shoes
Dust impervious protective suit
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).
Discard gloves that show tears, pinholes, or signs of wear.

Hygiene measures : Avoid breathing dust.
Wash hands before breaks and at the end of workday.
When using do not eat or drink.
Ensure that eyewash stations and safety showers are close to the workstation location.
When using do not smoke.

		Page: 7
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
		SDS Number: R1600370
CAN HTH EXTRA DURATION PUCKS		Version: 1.2
891045		

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	tablet
Color	:	blue
Odor	:	chlorine-like
Odor Threshold	:	No data available
pH	:	11.86 - 11.88 (25 °C) Concentration: 1 % (aqueous suspension)
Melting point/freezing point	:	Not applicable
Initial boiling point and boiling range	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not combustible Dust
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	No data available
Density	:	0.95 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available

		Page: 8
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
		SDS Number: R1600370
CAN HTH EXTRA DURATION PUCKS		Version: 1.2
891045		

Decomposition temperature : No data available

Viscosity
 Viscosity, dynamic : Not applicable

Viscosity, kinematic : No data available

Oxidizing properties : The substance or mixture is classified as oxidizing with the category 2.

Molecular weight : 143 g/mol

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under recommended storage conditions.

Conditions to avoid : Avoid heat, open flame, and prolonged storage at elevated temperatures.
 excessive heat
 Exposure to moisture.

Keep away from heat, flame, sparks and other ignition sources.

Incompatible materials : Do not allow product to come in contact with other materials, including e.g. other pool treatment products, acids, organic materials, nitrogen-containing compounds, dry powder fire extinguishers (containing mono-ammonium phosphate), oxidizers, all corrosive liquids, flammable or combustible materials, etc. A chemical reaction with such substances can cause a fire.

If product is exposed to small amounts of water, it can react violently to produce heat and toxic gases and spatter.

Hazardous decomposition products : Chlorine

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity


Harmful if swallowed.

Components:

CALCIUM HYPOCHLORITE:

Acute oral toxicity : LD50 (Rat): 850 mg/kg

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

		Page: 9
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
CAN HTH EXTRA DURATION PUCKS		SDS Number: R1600370
891045		Version: 1.2

Acute dermal toxicity : LD50 (Rabbit): > 2 g/kg

CALCIUM HYDROXIDE:

Acute inhalation toxicity : Remarks: Corrosive to respiratory system.

CALCIUM CHLORIDE:

Acute oral toxicity : LD50 (Rat): 2,301 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

CALCIUM CARBONATE:

Acute oral toxicity : LD50 (Rat): 6,450 mg/kg

Acute inhalation toxicity : LC 50 (Rat): > 3 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: Not classified as acutely toxic by inhalation under GHS.
 Remarks: Aerosol

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks : Causes severe skin burns and eye damage.

Components:

CALCIUM HYPOCHLORITE:

Result : Corrosive after 3 minutes to 1 hour of exposure

CALCIUM HYDROXIDE:


Result : Irritating to skin

CALCIUM CHLORIDE:

Result : Not irritating to skin

CALCIUM CARBONATE:

Result : Not irritating to skin

		Page: 10
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
		SDS Number: R1600370
CAN HTH EXTRA DURATION PUCKS		Version: 1.2
891045		

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

CALCIUM HYPOCHLORITE:

Result : Corrosive to eyes

CALCIUM HYDROXIDE:

Result : Corrosive to eyes

CALCIUM CHLORIDE:

Result : Severely irritating to eyes

CALCIUM CARBONATE:

Result : Not irritating to eyes

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

Components:

CALCIUM HYPOCHLORITE:


Assessment : May cause respiratory irritation.

CALCIUM HYDROXIDE:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

		Page: 11
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
CAN HTH EXTRA DURATION PUCKS		SDS Number: R1600370
891045		Version: 1.2

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

CALCIUM HYPOCHLORITE:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.049 - 0.16 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.067 mg/l
Exposure time: 48 h

CALCIUM CHLORIDE:

Toxicity to fish : LC50 (Bluegill (Lepomis macrochirus)): 9,500 mg/l
Exposure time: 96 h
Method: Static
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : LC 50 (Water flea (Ceriodaphnia dubia)): 1,770 - 2,030 mg/l
Exposure time: 48 h
Method: Static
Remarks: Mortality

CALCIUM CARBONATE:

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): > 56,000 mg/l
Exposure time: 96 h
Test Type: static test

Persistence and degradability


Components:

CALCIUM HYPOCHLORITE:

Biodegradability : Result: The methods for determining biodegradability are not applicable to inorganic substances.

CALCIUM HYDROXIDE:

Biodegradability : Result: The methods for determining biodegradability are not applicable to inorganic substances.

		Page: 12
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
CAN HTH EXTRA DURATION PUCKS		SDS Number: R1600370
891045		Version: 1.2

CALCIUM CHLORIDE:

Biodegradability : Result: The methods for determining biodegradability are not applicable to inorganic substances.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION


International Regulations

IATA-DGR

UN number : UN 2880
 Proper shipping name : Calcium hypochlorite, hydrated mixture
 Class : 5.1
 Packing group : III
 Packing instruction (cargo aircraft) : 563
 Packing instruction (passenger aircraft) : 559

IMDG-Code

UN number : UN 2880

		Page: 13
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
CAN HTH EXTRA DURATION PUCKS		SDS Number: R1600370
891045		Version: 1.2

Proper shipping name : CALCIUM HYPOCHLORITE, HYDRATED MIXTURE
 Class : 5.1
 Packing group : III
 EmS Code : F-H, S-Q
 Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 2880
 Proper shipping name : CALCIUM HYPOCHLORITE, HYDRATED MIXTURE
 Class : 5.1
 Packing group : III
 ERG Code : 140
 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:


TCSI : On the inventory, or in compliance with the inventory
 TSCA : Exempt
 AIC : On the inventory, or in compliance with the inventory
 DSL : Exempt
 ENCS : On the inventory, or in compliance with the inventory
 KECI : On the inventory, or in compliance with the inventory
 PICCS : On the inventory, or in compliance with the inventory
 IECSC : On the inventory, or in compliance with the inventory

Canadian lists

Exempt- This product is exempt from Significant New Activity Notification requirements. See information under Biocides for product registration information."

SECTION 16. OTHER INFORMATION

Further information

		Page: 14
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
		SDS Number: R1600370
CAN HTH EXTRA DURATION PUCKS		Version: 1.2
891045		


Revision Date : 12/26/2024

Full text of other abbreviations

- CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
- CA BC OEL : Canada. British Columbia OEL
- CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
- CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
- CA AB OEL / TWA : 8-hour Occupational exposure limit
- CA BC OEL / TWA : 8-hour time weighted average
- CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
- CA QC OEL / TWA EV : Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet
 Key literature references and sources of data
 SOLENIS Internal data

		Page: 15
SAFETY DATA SHEET		Revision Date: 12/26/2024
		Print Date: 10/28/2025
		SDS Number: R1600370
CAN HTH EXTRA DURATION PUCKS		Version: 1.2
891045		

SOLENIS internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This SDS has been prepared by the Solenis Environmental Health and Safety Department.

CA / EN